

LoRa Monitoring System

24/7/365 Warehouse Management

Temperature and Humidity Measurement
5km Long Distance
3 Years Battery Life



Features:

- * **Maximum 5km long distance measurement**
- * **Backup battery for emergency use**
- * **100pcs sensor tags could be recognized at a time**
- * **Easily USB/SMS configuration**
- * **Temperature and humidity alarm notification**
- * **Low battery level notification**
- * **RS485/Modbus-RTU/audible and visual device supported**
- * **LED light indicating for different status**

LoRa Gateway



Specifications:

Dimension	112mm*105mm*27mm (4.41in*4.13in*1.06in)
N.W	270g
Inner Lithium Battery	Built-in 3.7V/850mAh (rechargeable)
Power Supply	DC12V
Exterior RF Antenna	Receive RF signal better
Maximum Range in Open Area	5km
Working Temperature Condition	-20°C ~ +60°C
Working Humidity Condition	5%RH ~ 95%RH (non-condensing)
GPRS Frequency	850/900/1800/1900MHz
RF Frequency	433/470/868/915MHz (optional)
Modulation	LoRa
Interface	GPRS/RS485/Modbus - RTU
Transmit Interval	1min ~ 60mins (user definable)
Sensitivity of Receiving	-148dBm
Low Voltage Alarm	Yes (user definable)
Temperature Alarm	Yes (user definable)

Features:

- * Maximum 5km Long distance measurement
- * Large battery works for up to 3 years
- * High precise temperature and humidity sensor
- * Easily USB configuration
- * Temperature and humidity alarm notification
- * Low battery level notification
- * Button trigger for quick data testing
- * LED light indicating for different status

LoRa Temp & RH Sensor



Specifications:

Dimension	106mm*57mm*33mm (4.17in*2.24in*1.30in)
N.W	135g
Inner Lithium Battery	Built-in 3.6V/3500mAh (non-rechargeable)
Battery Working Life	3 years (in 15mins interval)
Accuracy of Temp and Humidity	Temp: $\pm 0.3^{\circ}\text{C}$ (0 ~ 60 $^{\circ}\text{C}$), $\pm 0.3 \sim 0.7^{\circ}\text{C}$ (other)
	Humidity: $\pm 3\%$ (20 ~ 80%), $\pm 4\%$ (other)
Exterior RF Antenna	Receive RF signal better
Maximum Range in Open Area	5km
Operating Temperature Range	-30 $^{\circ}\text{C}$ ~ +60 $^{\circ}\text{C}$
Operating Humidity Condition	0%RH ~ 85%RH (non-condensing)
RF Frequency	433/470/868/915MHz (optional)
Modulation	LoRa
Transmit Power	20dbm (adjustable)
Transmit Interval	1min ~ 1440mins (user definable)
Low Voltage Alarm	Yes (user definable)
Temperature/RH Alarm	Yes (user definable)
Standby Current	<5uA
Waterproof Level	IP54



Tzone Digital Technology Co., Ltd

Tel: +86-755-82840647 Fax: +86-755-82840648 Email: sales@tzone-digital.com Web: www.tzone-digital.com

Address: 16D, Haiying Building, South of Caitian Road, Futian District, Shenzhen, China, 518033